TREAD BOLDLY HOWE X HOWE FIRE DEPARTMENT FIREFIGHTING ROBOT QUOTE SHEET

Thank you for your interest in Thermite. Please review our standard equipment list and select the appropriate options to receive a detailed quote.

# **THERMITE**

FIREFIGHTING ROBOT

CONTACT NAME					
DATE					
COMPANY/ORGANIZATION					
ADDRESS					
PHONE					
E-MAIL					
MODEL INTEREST	RS1	Quantity	RS3	Quantity	

### PLEASE SUBMIT COMPLETED FORMS VIA E-MAIL:

firesales@howeandhowe.com

THANK YOU AND WE LOOK FORWARD TO YOUR RESPONSE!

# THERMITE RS1

# STANDARD EQUIPMENT

### CHASSIS

- > Aluminum chassis
- > Chassis color: yellow
- > Base height 64 in
- > Base width 44 in
- > Base length 72 in
- > Hydrostatic drive
- > Diesel engine 24 hp liquid cooled Kohler
- > 12 volt DC 30 AMP alternator
- > Battery maintainer included
  - Input voltage 110 to 250 VAC 50/60 hz
- > Maximum speed 8 mph
- > Fuel tank 9 gal
- > Winch 5,000 lb
- > Rear hitch
- > Tool/cargo crib
- > Locking canopy

### ELECTRONICS

- Radio control belly pack control with video screen
- > Video System
  - · Tethered control included
  - Tethered maximum distance 100 ft
  - · High definition standard (1080p) front
  - High definition standard (1080p) rear

### MONITOR

> Elkhart Brass 7,200 Cobra EXM Remote monitor nozzle 1,000-1,250 gpm

### LIGHTING

- > Front
- > Real
- > Emergency flasher, dual color

### PLUMBING

- > Inlet line size 3" NPT (qty 2)
- > Aux take-off 2.5" NPT (qty 2)
- > Self-cooling spray system
- Bumper sprayers

# AVAILABLE OPTIONS

\*INCLUDED WITH STANDARD PRICING

## CHASSIS COLOR

Yellow\*

Red

Other

Specify colors

### VIDEO SYSTEM

Front/rear rigid mounted camera\* Additional monitor mounted camera Thermal camera - special licensing may be required

## REMOTE SHUT OFF VALVE

No\*

Yes

## EMERGENCY FLASHERS

- > Two flashers\*
- Two additional flashers
- Dual color
- Dual color
- Specify colors
- Specify colors

# THERMITE RS3

# STANDARD EQUIPMENT

#### CHASSIS

- > Aluminum chassis
- > Chassis color: yellow
- > Base height 48.5 in
- > Base width 65.5 in
- > Base length 91.5 in
- > Hydrostatic drive
- > Diesel engine 37 hp liquid cooled Yanmar
- > 12 volt DC 45 AMP alternator
- > Battery maintainer included
  - Input voltage 110 to 250 VAC 50/60 hz
- > Maximum speed 8 mph
- > Fuel tank 8 gal
- > Winch 8,000 lb
- > Rear hitch
- > Dual tool/cargo crib
- > Locking canopy

#### ELECTRONICS

- Radio control belly pack control with video screen
- > Video System
  - Tethered control included
  - Tethered maximum distance 100 ft
  - High definition standard (1080p) front
  - · High definition standard (1080p) rear

### MONITOR

 Elkhart Brass 7,400 Scorpion EXM Remote monitor nozzle 2,500 gpm

#### LIGHTING

- > Front
- > Rear
- > Emergency flasher, dual color

### PLUMBING

- Bumper sprayers
- > Inlet Line Size (qty 7)
  - Seven 3" NPT
- Remote auxiliary water outlet
- > Remote water valve
- Self-cooling spray system

# AVAILABLE OPTIONS

\*INCLUDED WITH STANDARD PRICING

### CHASSIS COLOR

Red

Yellow\*

Other

Specify colors

### EMERGENCY FLASHERS

> Two flashers\*

Dual color

Two additional flashers

Dual color

Specify colors

Specify colors

## VIDEO SYSTEM

Front/rear rigid mounted camera\* Additional monitor mounted camera Thermal camera - special licensing may be required

### PLUMBING

> Layout

Seven inlets\*
Five inlets with two outlets

Inlet type/size

3" NPT\* Other

Specify type/size

### VENTILATOR

- Electric actuated raise/lower and tilt function
- > Water spray 62 gpm
- > Air flow 9,200 cfm
- > Height with ventilator attachment retracted (min clearance) 87.75 in
- Height with ventilator attachment extended (max height) 110 in

## V-PLOW

- Hydraulic actuated raise/ lower function
- > Vehicle width 65.5 in
- Overall vehicle length with plow assembly 115.5 in