TREAD BOLDLY HOWE X HOWE FIRE DEPARTMENT FIREFIGHTING ROBOT QUOTE SHEET

ripsawsales@howeandhowe.com

Thank you for your interest in Thermite. Please review our standard equipment list and select the appropriate options to receive a detailed quote.

THERMITE

FIREFIGHTING ROBOT

CONTACT NAME					
DATE					
COMPANY/ORGANIZATION					
ADDRESS					
PHONE					
E-MAIL					
MODEL INTEREST	RS1	Quantity	RS3	Quantity	

PLEASE SUBMIT COMPLETED FORMS VIA E-MAIL:

firesales@howeandhowe.com

THANK YOU AND WE LOOK FORWARD TO YOUR RESPONSE!

THERMITE RS1

STANDARD EQUIPMENT

CHASSIS

- > Aluminum chassis
- > Chassis color: yellow
- > Base height 64 in
- > Base width 44 in
- > Base length 72 in
- > Hydrostatic drive
- > Diesel engine 24 hp liquid cooled Kohler
- > 12 volt DC 30 AMP alternator
- > Battery maintainer included
 - Input voltage 110 to 250 VAC 50/60
- > Maximum speed 8 mph
- > Fuel tank 9 gal
- > Winch 5,000 lb
- > Rear hitch
- > Tool/cargo crib
- > Locking canopy

ELECTRONICS

- Radio control belly pack control with video screen
- Video System
 - · Tethered control included
 - Tethered maximum distance
 100 ft
 - High definition standard (1080p) front
 - High definition standard (1080p) rear

MONITOR

> Elkhart Brass 7,200 Cobra EXM Remote monitor nozzle 1,000-1,250 gpm

LIGHTING

- > Front
- > Rear
- > Emergency flasher, dual color

PLUMBING

- > Inlet line size 3" NPT (qty 2)
- Aux take-off 2.5" NPT (qty 2)
- > Self-cooling spray system
- > Bumper sprayers

AVAILABLE OPTIONS

*INCLUDED WITH STANDARD PRICING

CHASSIS COLOR

Yellow* Red

Other

Specify colors

EMERGENCY FLASHERS

> Two flashers*

Two additional flashers

Dual color

Specify colors

Dual color

Specify colors

WINCH SIZE

5,000 lb*

8,000 lb

REMOTE SHUT OFF VALVE

No*

Yes

VIDEO SYSTEM

Front/rear rigid mounted camera* Additional monitor mounted camera Thermal camera - special licensing may be required

THERMITE RS3

STANDARD EQUIPMENT

CHASSIS

- Aluminum chassis
- Chassis color: yellow
- Base height 48.5 in
- Base width 65.5 in
- Base length 91.5 in
- Hydrostatic drive
- Diesel engine 37 hp liquid cooled Yanmar
- 12 volt DC 45 AMP alternator
- Battery maintainer included
 - Input voltage 110 to 250 VAC 50/60 hz
- Maximum speed 8 mph
- Fuel tank 8 gal
- Winch 8,000 lb
- Rear hitch
- Dual tool/cargo crib
- Locking canopy

ELECTRONICS

- Radio control belly pack control with video
- Video System
 - Tethered control included
 - Tethered maximum distance 100 ft
 - High definition standard (1080p) front
 - High definition standard (1080p) rear

MONITOR

Elkhart Brass 7,400 Scorpion EXM Remote monitor nozzle 2,500 gpm

LIGHTING

- Front
- Rear
- Emergency flasher, dual color

PLUMBING

- Bumper sprayers
- Inlet Line Size (qty 7)
 - Seven 3" NPT
- Remote auxiliary water outlet
- Remote water valve
- Self-cooling spray system

AVAILABLE OPTIONS

*INCLUDED WITH STANDARD PRICING

CHASSIS COLOR

Yellow*

Red

Other

Specify colors

EMERGENCY FLASHERS

Two flashers*

Dual color

Two additional flashers

Dual color

Specify colors

Specify colors

VIDED SYSTEM

Front/rear rigid mounted camera* Additional monitor mounted camera Thermal camera - special licensing may be required

WINCH SIZE

8,000 lb*

12,000 lb

PLUMBING

Layout

Seven inlets* Five inlets with two outlets

Inlet type/size

3" NPT* Other

Specify type/size

VENTILATOR

- Electric actuated raise/lower and tilt function
- Water spray 62 gpm
- Air flow 9,200 cfm
- Height with ventilator attachment retracted (min clearance) 87.75 in
- Height with ventilator attachment extended (max height) 110 in

V-PLOW

- Hydraulic actuated raise/ lower function
- Vehicle width 65.5 in
- Overall vehicle length with plow assembly 115.5 in